



Enhance the elegance and privacy of your glass with our high-quality 6mm frosted reeded glass film. Our film replicates the timeless look of reeded glass, offering a stylish and functional solution for your home or office. Enjoy the beauty of diffused light while maintaining your desired level of privacy. Our reeded glass film is easy to install, durable, and designed to last.



**10 YEARS**



Fire-resistance rating  
**MI**



Storage from -5°C to +40°C  
**3 YEARS**



REACH RoHS compliant  
**RESPECTED**

### TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	0.5 %
Visible light transmission	84 %
Reflection of external visible light	9 %
Reflection of internal visible light	9 %
Total solar energy rejected	14 %
Total solar energy rejected 2*	15 %
Solar ratio :	
Solar energy reflection	9 %
Solar energy absorption	7 %
Solar energy transmission	84 %
Reduction in Solar Glare	13 %
g-value	0.85
u-value	
Shading coefficient	0.9
Installation type : Interior	
Roll length	Various
Film composition	PET
Thickness	50 µ

Colour from the outside :  
 TRANSPARENT

### CONSTRUCTION

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality polyester
3. Bonding adhesive
4. High optical quality polyester
5. PS adhesive, glass polymerization within 15 days
6. Protection release liner, disposable after installation



### MAINTENANCE INSTRUCTIONS

Soapy water solution, do not clean for at least a month.

Non-contractual data, Abode Window Films reserve the right to modify the composition of its films at any times.

### INSTALLATION ADVICE

Vertical installation and on standard glass surface\*

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes    ! Caution    ✗ Not recommended

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>.