




Exterior

Interior



TOTAL UV 400

UV CONTROL

Description

Total UV 400 Window Film provides near-complete protection across the entire ultraviolet spectrum, blocking virtually 100% of harmful UVA and UVB rays as well as high-energy light wavelengths up to 400–420 nanometres. Engineered for superior preservation, this advanced UV protection window film helps prevent fading and deterioration of furnishings, artwork, displays, textiles, and valuable interior finishes.

As an additional UV management measure, UV 400 window film may benefit individuals seeking to reduce exposure to sunlight-related wavelengths, including those with photosensitive or sun-sensitive skin conditions. The film blocks virtually 100% of UV rays while preserving natural daylight and clear visibility.



Visible Light Transmission (%)




Visible Light Reflection - External (%)



UV Rejection (%)



Total Solar Energy Rejected (%)



0 10 20 30 40 50 60 70 80 90 100

||| 3 mm simple glazing - without film ■ Film applied to 3 mm simple glazing

Characteristics


-  **Warranty**
10 years
-  **Fire Resistance Rating**
M1
-  **Storage in recommended conditions**
3 years
-  **REACH / RoHS**
Compliant
-  **Widths Available**
152 cm
-  **Installation Type**
Interior
-  **Color From the Outside**
Light Grey
-  **Length**
30.5 m
-  **Product Carbon Footprint (LCA)**
1.56 kgCO₂e/m²

Construction

- 1 Scratch-resistant hard coating providing surface protection, durability, and ease of cleaning
- 2 High optical quality polyester, with an IR-blocking metallic particle coating
- 3 Bonding adhesive
- 4 High optical quality polyester
- 5 PS adhesive, polymerizes with glass within 15 days
- 6 Protection PET release liner, disposable after installation

-  **Composition**
PET
-  **Thickness**
50 µm

Details



Energy and environmental benefits⁰¹

-  **Energy savings**
N/A
-  **Carbon footprint reduction**
N/A
-  **Financial savings**
N/A

Optical and solar properties

Pane type	Single 3mm		Double Low-E	
	No film	With Film	No film	With Film
UV Rejection (%)	25	100	40	100
Visible Light Transmission (%)	91	70	82	63
Visible Light Reflection - External (%)	8	10	11	15
Visible Light Reflection - Internal (%)	8	11	12	14
Solar Energy Reflection (%)	5	9	28	24
Solar Energy Absorption (%)	8	35	12	40
Solar Energy Transmission (%)	87	56	60	36
Total Solar Energy Rejected (%)	12	42	35	40
Glare Reduction (%)	-	26	-	16
Shading Coefficient	-	0.70	-	0.75
g-value	0.88	0.62	0.65	0.65
U-value (W/m ² .°C)	5.8	5.6	1.1	1.1

Application advice⁰²

Vertical situation and for a standard glazed surface

- Clear Single Pane ✓
- Tinted Single Pane ✓
- Reflective Tinted Single Pane ✓
- Clear Double Pane ✓
- Tinted Double Pane ✓
- Reflective Tinted Double Pane ✓
- Gas-Filled Double Pane - Low E ✓
- Stadip Ext. Clear Double Pane ✓
- Stadip Int. Clear Double Pane !

✓ Yes ✗ Not recommended ! Caution

Installation and Maintenance Advise

You can easily make your own installation fluid at home. Mix 1 liter of water with about 8 drops of baby shampoo or a mild, clear dish soap for installation and cleaning. Do not clean for one month after installation or apply stickers/adhesives on the film.



Access the installation and maintenance advice video

01 Values based on a study carried out on an air-conditioned building located in Luxembourg, with a film applied on a low-E double glazing, facing East. The heating months considered are from October to March, and the cooling months from April to September. We consider an electric heating system of the heat pump type, with a production efficiency of 3.5 and an electric cooling system with an efficiency of 3. For more information, visit our online tool.

02 Advice based on glazed surface area up to 2.5 m², please contact us for any confirmation or thermal shock analysis.

The data in this information sheet is not contractual, we reserves the right to modify the composition of its products at any time. Please refer to our warranties and general sales conditions.